




3CORES 16AWG SHIELDED CABLES - FR- PVC, LSZH

PRODUCT NO.: BMS/3150

DESCRIPTION: Stranded copper cables for BMS & Audio

The KAYBE 3-Core 16AWG Shielded Speaker Cable ensures premium audio clarity with shielding to reduce interference. Built with FR-PVC and LSZH-rated jacketing, it provides fire resistance, low smoke emissions, and halogen-free safety. Perfect for high-quality audio installations in residential, commercial, and industrial environments.



STANDARD REFERENCES

UL Rating	CMR
UL Flammability	UL 1666 Vertical Shift
ISO/IEC Flammability	IEC 60332-1
UL Voltage Rating	300V RMS
Certification	CE ROHS certified

PACKAGING

Packaging	305M Wooden Spool x 2 Drums per box
Weight	5 Kg/roll

CONSTRUCTION DATA SHEET

Item	Audio & Security Cable
CONDUCTOR	
Conductor	3 Cores
Material	Bare Copper
AWG	16 AWG
Structure	19x29
INSULATION	
Material	PE
Average Thickness	0.40mm
Diameter	1.75mm + 0.05 mm
RIP Cord	Yes, Nylon
PE Color	1. Black Color 2. Red Color 3. White Color
SHIELDING	
Polytape	100% coverage
Alu Tape Foil	100% coverage
Drain Wire	7x30 (22awg)
OUTER JACKET	
Material	FR-PVC, LSZH
Average Thickness	0.83mm
Diameter	5.10 + 0.2mm
Color	Grey
PRINTING	KAYBE Speaker & Control Cable (BMS/3150) 305M..
LENGTH	305METERS (1000FT)

ELECTRICAL & MECHANICAL PARAMETERS

Tensile Strength N/mm2	10.00 (Min.)
Elongation %	100 (Min.)
Heat Shock 150±20C for 1 hrs.	No Crack
Hot Deformation (75±20C for 4hrs)	50 (Max)
Cold Bend -20± 20C Deg. C for (2~3 Hrs.)	No Crack
Temperature Rating	-20°C To +75°C
Operating Voltage	300V RMS Max.
Dc Resistance	51.2 Ω/km
Capacitance Between conductor to Shield1Khz	125 pF/ft Nom

ORDERING INFORMATION AS PER FOLLOWS

PART NO	DESCRIPTION	COLOR	WEIGHT
BMS/3150SH	3CORES 16AWG, SPEAKER CABLES, FR PVC, SHIELDED	Grey	52kg/km
BMS/3150SH-LS	3CORES 16AWG, SPEAKER CABLES, LSZH, SHIELDED	Purple	54kg/km